














	INTERIOR DIMENSIONS	DOOR OPENING	TOP OPENING	TARE WEIGHT	CUBIC CAPACITY	PAYLOAD
20« DRY FREIGHT 	L: 5,896 mm W: 2,350 mm H: 2,393 mm	W: 2,340 mm H: 2,274 mm		2,280 kg 5,030 lbs	33.0 cbm 1,179 cu ft	28,200 kg 62,170 lbs
40« DRY FREIGHT 	L: 12,032 mm W: 2,350 mm H: 2,393 mm	W: 2,340 mm H: 2,274 mm		3,700 kg 8,157 lbs	67 cbm 2,390 cu ft	28,800kg 63,493lbs
40« HIGH CUBE 	L: 12,032 mm W: 2,350 mm H: 2,697 mm	W: 2,340 mm H: 2,577 mm		3,880 kg 8,550 lbs	76 cbm 2,700 cu ft	28,620kg 63,100 lbs
45« HIGH CUBE 	L: 13,556 mm W: 2,350 mm H: 2,697 mm	W: 2,340 mm H: 2,585 mm		4,900 kg 10,800 lbs	86 cbm 3,040 cu ft	27,600 kg 60,850 lbs
20« REEFER 	L: 5,451 mm W: 2,290 mm H: 2,167 mm	W: 2,290 mm H: 2,212 mm		2,990 kg 6,591 lbs	27 cbm 995 cu ft	27,490 kg 60,603 lbs
40« REEFER 	L: 11,578 mm W: 2,280 mm H: 2,425 mm	W: 2,278 mm H: 2,473 mm		4,200 kg 9,259 lbs	64 cbm 2,261 cu ft	29,800 kg 65,698 lbs
40« HIGH CUBE REEFER 	L: 11,578 mm W: 2,280 mm H: 2,425 mm	W: 2,276 mm H: 2,471 mm		4,400 kg 9,700 lbs	64 cbm 2,250 cu ft	29,600 kg 65,527 lbs
20« OPEN TOP 	L: 5,919 mm W: 2,340 mm H: 2,286 mm	W: 2,286 mm H: 2,251 mm	L: 5,425 mm W: 2,223 mm	2,177 kg 4,799 lbs	32 cbm 1,143 cu ft	21,823 kg 48,110 lbs
20« FLAT RACK 	L: 5,935 mm W: 2,398 mm H: 2,327 mm			2,560 kg 5,644 lbs		21,400 kg 47,267 lbs
20« COLLAPSIBLE RACK 	L: 5,966 mm W: 2,418 mm H: 2,286 mm			2,970kg 6,547 lbs		27,510 kg 60,647 lbs
40« OPEN TOP 	L: 12,029 mm W: 2,348 mm H: 2,359 mm	W: 2,338 mm H: 2,275 mm	L: 11,622 mm W: 2,188 mm	3,800 kg 8,378 lbs	66 cbm 2,355 cu ft	28,700 kg 63,273 lbs
40« FLAT RACK 	L: 12,080 mm W: 2,438 mm H: 2,103 mm			5,480 kg 12,081 lbs		25,000 kg 55,116 lbs
40« COLLAPSIBLE RACK 	L: 12,178 mm W: 2,365 mm H: 1,943 mm			5,200 kg 11,464 lbs		39,800 kg 87,744 lbs

NB: Shipper Owned Containers with a valid CSC Plate will be accepted. Contact local Customer Service Team for more information.